

Flashings Automatic Performance Guarantee

This is a two page document

This guarantee covers the time before a building owner needs to repaint the Colorcoat® pre-finished steel flashings for the duration indicated in the matrix below. Any colour fade or colour change shall be limited and uniform given equal exposure to the local environmental conditions.


The guarantee is issued by Tata Steel Colors through the Colorcoat® Accredited Distributor on an application specific basis. Any claims on the guarantee should be made through the contractual supply chain and not made directly to Tata Steel Colors. Full material traceability must be provided.

Customer: Capital Coated Steel

Guarantee number: SP4707

Date of guarantee: 19th June 2015

Signed:


 David W Cooper, CTS Manager

Colorcoat® products guarantee cover

Product	Colour band	Roof elevation	Inland years		Coastal years	
			Walls	Roof	Walls	Roof
Colorcoat® LG	CD1	4 degrees	25	25	20	20
	CD2	4 degrees	20	15	15	10

Notes

1. Guarantee periods quoted are applicable for UK and Ireland only.
2. Figures under coastal heading are buildings within 2km of the sea.

Terms and conditions

Limitations

1. The material has to be installed on the building within 12 calendar months after shipment from Tata Steel Colorcoat® manufacturing works, Shotton.
2. Tata Steel Colors has to be notified by the Colorcoat® Accredited Distributor of a claim in writing within 30 days of the identification of any defect indicating a (potential) failure of the product meeting its performance criteria and, for any single plane, before 10% or 200 square metres of the paint surface, whichever is the lesser, is affected. Notification must include proof of the origin of the product including Tata Steel coil number and tracking information on the manufacturing and installation of the product.
3. Tata Steel Colors obligation under this guarantee is limited exclusively to the cost of flat sheet material as supplied to the Colorcoat® Accredited Distributor for re-manufacture of replacement flashings. Under no circumstances shall Tata Steel Colors be liable for any indirect or consequential costs, loss or damage.
4. All longitudinal edges of flashings must be subject to best practice i.e. welded (folded) or lock-rolled, such that longitudinal sheared edges are not exposed to weathering or are not on view.
5. The warranty holds for this application only.
6. Buildings should be inspected annually and maintained in line with published literature.
7. The warranty applies only to deterioration of the weather side of the Colorcoat® product. Corrosion or other effects arising from elements within the building, corrosion from entrapment of pollutants within overlaps or from abnormal atmospheric pollution and contact with aggressive fumes or chemicals are excluded.
8. Installation, processing and use of the material has to be in accordance with the current product literature and published best practice at the date of sale.
9. Appropriate accessories and material have to be used to prevent any acceleration of corrosion of the weathering sheets.
10. The warranty is subject to English law.

Trademarks of Tata Steel UK Limited

Colorcoat and Colorcoat Connection are registered trademarks of Tata Steel UK Limited.

Tata Steel registered office:
30 Millbank, London, SW1P 4WY
Registered in England No. 2280000

Copyright 2015

Exclusions

1. Fabrication and/or installation of the pre-finished steel at temperatures other than indicated in the current product data sheet at the time of sale.
2. The performance of any touch-up paint or over-paint used on the flashings.
3. Fire, lightning, flood, explosion, abnormal winds, earthquake, acts of war, riots, civil commotion, radiation, falling objects, vandalism and other extraneous causes.
4. Misuse, wilful act or negligence.
5. Damage to the sheets incurred during fabricating, storage, transport or erection.
6. Accumulations of dirt or debris, nor does it apply to failure or damage in areas not exposed to washing by rainfall unless, in each case, the maintenance records should show clearly that these areas have been adequately hosed down at least annually.
7. Emissions of harmful gases, fumes or chemicals from either natural or man-made sources at or within 400 metres of the original erection site.
8. Exposure to continuous temperatures howsoever caused greater than stated in the product data sheet at the date of sale.
9. Deterioration caused by contact with wet, green or treated timber or due to direct or indirect contact with corrosive materials.
10. Any alteration or modification to Colorcoat® pre-finished steel after erection.

In the event of a claim, please contact:

Capital Coated Steel Ltd
North Blackvein Industrial Estate
Wattsville
Newport
NP11 7PX
T: +44 (0)1495 814000

Technical enquiries

Colorcoat Connection® helpline
T: +44 (0)1244 892434
F: +44 (0)1244 892321
E: colorcoat.connection@tatasteel.com
W: www.colorcoat-online.com